KZN Health > Components > Supply Chain Management

# AdvertQuote

KWAZULU-NATAL PROVI MEALTH REPUBLIC OF SOUTH AFRICA	NCE Quotation Advert	
Opening Date:	2022-09-02	
Closing Date:	2022-09-13	
Closing Time:	11:00	
INSTITUTION DETAILS		
Institution Name:	llembe district office	V
Province:	KwaZulu-Natal	
Department or Entity:	Department of Health	
Division or section:	Central Supply Chain Management	
Place where goods / services is required	Mpumelelo Clinic	
Date Submitted	2022-09-02	0
ITEM CATEGORY AND DETAILS		
Quotation Number:	ZNQ: 1.6/ LEM/107/22/23	
Item Category:	Services	~
Item Description:	Alterations to accommodate reception area at Mpumelelo Clinic as per attached specification  NB: CIDB grading 1GB and above	
Quantity (if supplies)	N/A	
COMPULSORY BRIEFING SESSION		
Select Type:	Compulsory Briefing Session	
Date :		_
Time:	2022-09-08	
Venue:	10h30am Mpumelelo Clinic	
QUOTES CAN BE COLLECTED FROM:	Attached to this advert or llembe Health District Office	
QUOTES SHOULD BE DELIVERED TO:	Tender box, ground floor next to elevators at No.1 King Shaka Street, uShaka Center Building, KwaDukuza 4450	
<b>ENQUIRIES REGARDING THE ADVE</b>	RT MAY BE DIRECTED TO:	
Name:	Sizwe Mabaso or Xolani Khumalo	
Email:	sizwe.mabaso@kznhealth.gov.za	
Contact Number:	032 - 437 3500	
Finance Manager Name:	Ms. H.V. Zulu	
Finance Manager Signature:	late quotes will be considered	

STANDARD QUOTE DOCUMENTATION OVER R30 000.00 YOU ARE HEREBY INVITED TO QUOTE FOR REQUIREMENTS AT: ILEMBE HEALTH DISTRICT OFFICE DATE ADVERTISED: 02 September 2022 .............. CLOSING TIME: 11:00 FACSIMILE NUMBER: 032 - 552 1889 sizwe.mabaso@kznhealth.gvo.za ...... E-MAIL ADDRESS: No.1 King Shaka Street, 2nd and 3rd floors, uShaka Center Building, KwaDukuza, 4450 PHYSICAL ADDRESS: QUOTE NUMBER: ZNQ / LEM **1** / 107 DESCRIPTION: Alterations to accommodate reception at Mpumelelo Clinic as per attached specification CONTRACT PERIOD A-hoc VALIDITY PERIOD 60 Days SARS PIN..... (if applicable) Μ CENTRAL SUPPLIER DATABASE REGISTRATION (CSD) NO. UNIQUE REGISTRATION REFERENCE DEPOSITED IN THE QUOTE BOX SITUATED AT (STREET ADDRESS) No. King Shaka Street, 2nd and 3rd floors, uShaka Center Building, KwaDukuza 4450 Bidders should ensure that quotes are delivered timeously to the correct address. If the quote is late, it will not be accepted for consideration. The quote box is open from 08:00 to 15:30. QUOTATIONS MUST BE SUBMITTED ON THE OFFICIAL FORMS - (NOT TO BE RETYPED) THIS QUOTE IS SUBJECT TO THE PREFERENTIAL PROCUREMENT POLICY FRAMEWORK ACT AND THE PREFERENTIAL PROCUREMENT REGULATIONS, 2011, THE GENERAL CONDITIONS OF CONTRACT (GCC) AND, IF APPLICABLE, ANY OTHER SPECIAL CONDITIONS OF CONTRACT, THE FOLLOWING PARTICULARS MUST BE FURNISHED (FAILURE TO DO SO MAY RESULT IN YOUR QUOTE BEING DISQUALIFIED) NAME OF BIDDER POSTAL ADDRESS STREET ADDRESS TELEPHONE NUMBER CODE......NUMBER......FACSIMILE NUMBER CODE ......NUMBER..... **CELLPHONE NUMBER** E-MAIL ADDRESS VAT REGISTRATION NUMBER (If VAT vendor) ..... HAS A B-BBEE STATUS LEVEL VERIFICATION CERTIFICATE BEEN SUBMITTED? (SBD 6.1) YES NO

[A B-BBEE STATUS LEVEL VERIFICATION CERTIFICATE/SWORN AFFIDAVIT (FOR EMES& QSEs) MUST BE SUBMITTED TO QUALIFY

FOR PREFERENCE POINTS FOR B-BBEEL

# OFFICIAL PRICE PAGE FOR QUOTATIONS OVER R30 000

QUOTE NUMBER: ZNQ/LEM 107 / 22 23

DESCRIPTI	ON: Alterati	ons to accommodate reception at Mpumelelo Clinic as pe	r attached spec	sification		
SIGNATURI	E OF BIDDE his documer	Rt, I hereby agree to all terms and conditions]	DATE			
		ICH THIS CHOTE IS SIGNED				
Item No	Quantity	Description	Brand &	Country of	Price	
			model	manufacture	R	С
01	01	Alterations to accommodate reception at Mpumelelo				
		Clinic as per attached specification				

Quality	Description	Brand &	Country of	Price	
		model	manufacture	R	С
01	Alterations to accommodate reception at Mpumelelo				
	Clinic as per attached specification				
	NB: CIDB 1GB AND ABOVE IS REQUIRED				T
					1
					$\top$
	COMPULSORY ATTACHMENTS:				T
	1. CERTIFIED COPY OF BBBEE CERTIFICATE				
	APPROVED BY SANAS (OR) EME SWORN				1
	AFFIDAVIT				
	2. CSD SUPPLIER'S SUMMARY REPORT				
					1
					T
					1
					Т
					T
	01	Clinic as per attached specification  NB: CIDB 1GB AND ABOVE IS REQUIRED  COMPULSORY ATTACHMENTS:  1. CERTIFIED COPY OF BBBEE CERTIFICATE APPROVED BY SANAS (OR) EME SWORN AFFIDAVIT	Clinic as per attached specification  NB: CIDB 1GB AND ABOVE IS REQUIRED  COMPULSORY ATTACHMENTS:  1. CERTIFIED COPY OF BBBEE CERTIFICATE  APPROVED BY SANAS (OR) EME SWORN  AFFIDAVIT	O1 Alterations to accommodate reception at Mpumelelo Clinic as per attached specification  NB: CIDB 1GB AND ABOVE IS REQUIRED  NB: CIDB 1GB AND ABOVE IS REQUIRED  COMPULSORY ATTACHMENTS:  1. CERTIFIED COPY OF BBBEE CERTIFICATE APPROVED BY SANAS (OR) EME SWORN  AFFIDAVIT	O1 Alterations to accommodate reception at Mpumelelo  Clinic as per attached specification  NB: CIDB 1GB AND ABOVE IS REQUIRED  NB: CIDB 1GB AND ABOVE IS REQUIRED  COMPULSORY ATTACHMENTS:  1. CERTIFIED COPY OF BBBEE CERTIFICATE  APPROVED BY SANAS (OR) EME SWORN  AFFIDAVIT

TOTAL QUOTATION PRICE (VALIDITY PERIOD 60 Days)

Does The Article Conform To The S.A.N.S. / S.A.B.S.

Does This Offer Comply With The Specification?	Specification?
Is The Price Firm?	State Delivery Period, e.g., 1day, 1week

Enquiries regarding the quote may be directed to:

Contact Person: SIZWE MABASO Tel: 032 - 437 3500

E-Mail Address: sizwe.mabaso@kznhealth.gov.za

Enquiries regarding technical information may be directed to:

Contact Person: NTOKOZO SIKHAKHANE Tel: 032 - 437 3500

### **BIDDER'S DISCLOSURE**

### 1. PURPOSE OF THE FORM

Any person (natural or juristic) may make an offer or offers in terms of this invitation to bid. In line with the principles of transparency, accountability, impartiality, and ethics as enshrined in the Constitution of the Republic of South Africa and further expressed in various pieces of legislation, it is required for the bidder to make this declaration in respect of the details required hereunder.

Where a person/s are listed in the Register for Tender Defaulters and / or the List of Restricted Suppliers, that person will automatically be disqualified from the bid process.

2.	BIDDER'S	DECL	ARAT	TON

- 2.1. Is the bidder, or any of its directors / trustees / shareholders / members / partners or any person having a controlling interest<sup>1</sup> in the enterprise, employed by the state?
- 2.1.1 If so, furnish particulars of the names, individual identity numbers, and, if applicable, state employee numbers of sole proprietor/directors / trustees / shareholders / members/ partners or any person having a controlling interest in the enterprise, in table below.

Full Name	Identity Number	Name of State Institution

- 2.2. Do you, or any person connected with the bidder, have a relationship with any person who is employed by the procuring institution?
- 2.2.1. If so, furnish particulars: .....
- 2.3. Does the bidder or any of its directors / trustees / shareholders / members / partners or any person having a controlling interest in the enterprise have any interest in any other related enterprise whether or not they are bidding for this contract? YES/NO
- 2.3.1. If so, furnish particulars: .....

#### 3. DECLARATION

- 3.1. I have read and I understand the contents of this disclosure;
- 3.2. I understand that the accompanying bid will be disqualified if this disclosure is found not to be true and complete in every respect;
- 3.3. The bidder has arrived at the accompanying bid independently from, and without consultation, communication, agreement or arrangement with any competitor. However, communication between partners in a joint venture or consortium<sup>2</sup> will not be construed as collusive bidding.
- 3.4. In addition, there have been no consultations, communications, agreements or arrangements with any competitor regarding the quality, quantity, specifications, prices, including methods, factors or formulas used to calculate prices, market allocation, the intention or decision to submit or not to submit the bid, bidding with the intention not to win the bid and conditions or delivery particulars of the products or services to which this bid invitation relates.
- 3.5. The terms of the accompanying bid have not been, and will not be, disclosed by the bidder, directly or indirectly, to any competitor, prior to the date and time of the official bid opening or of the awarding of the contract.
- 3.6. There have been no consultations, communications, agreements or arrangements made by the bidder with any official of the procuring institution in relation to this procurement process prior to and during the bidding process except to provide clarification on the bid submitted where so required by the institution; and the bidder was not involved in the drafting of the specifications or terms of reference for this bid.
- 3.7. I am aware that, in addition and without prejudice to any other remedy provided to combat any restrictive practices related to bids and contracts, bids that are suspicious will be reported to the Competition Commission for investigation and possible imposition of administrative penalties in terms of section 59 of the Competition Act No 89 of 1998 and or may be reported to the National Prosecuting Authority (NPA) for criminal investigation and or may be restricted from conducting business with the public sector for a period not exceeding ten (10) years in terms of the Prevention and Combating of Corrupt Activities Act No 12 of 2004 or any other applicable legislation.

I CERTIFY THAT THE INFORMATION FURNISHED IN PARAGRAPHS 1, 2 and 3 ABOVE IS CORRECT.

I ACCEPT THAT THE STATE MAY REJECT THE BID OR ACT AGAINST ME IN TERMS OF PARAGRAPH 6 OF PFMA SCM INSTRUCTION 03 OF 2021/22 ON PREVENTING AND COMBATING ABUSE IN THE SUPPLY CHAIN MANAGEMENT SYSTEM SHOULD THIS DECLARATION PROVE TO BE FALSE.

Name of Bidder Signature Position	Date
-----------------------------------	------

<sup>1</sup> the power, by one person or a group of persons holding the majority of the equity of an enterprise, alternatively, the person/s having the deciding vote or power to influence or to direct the course and decisions of the enterprise.

<sup>2</sup> Joint venture or Consortium means an association of persons for the purpose of combining their expertise, property, capital, efforts, skill and knowledge in an activity for the execution of a contract.

#### **GENERAL CONDITIONS OF CONTRACT**

#### 1. AMENDMENT OF CONTRACT

1.1. Any amendment to or renunciation of the provisions of the contract shall at all times be done in writing and shall be signed by both parties.

### 2. CHANGE OF ADDRESS

2.1. Bidders must advise the Department of Health (institution where the offer was submitted) should their address (domicilium citandi et executandi) details change from the time of bidding to the expiry of the contract.

# 3. GENERAL CONDITIONS ATTACHED TO THIS QUOTATION

- 3.1. The Department is under no obligation to accept the lowest or any quote.
- 3.2. The Department reserves the right to communicate in writing with vendors in cases where information is incomplete or where there are obscurities regarding technical aspects of the offer, to obtain confirmation of prices or preference claims in cases where it is evident that a typing, written, transfer or unit error has been made, to investigate the vendor's standing and ability to complete the supply/service satisfactorily.
- 3.3. ALL DECISIONS TAKEN BY THE DEPARTMENT ARE FINAL, INCLUDING THE AWARD OR CANCELLATION OF THIS QUOTATION.
- 3.4. The price quoted must include VAT (if VAT vendor).
- 3.5. Should a bidder become a VAT vendor after award or during the implementation of a contract, they may not request the VAT percentage from the Department as the service provider made an offer during the period they were not registered as a VAT vendor. The Department is only liable for any VAT from registered VAT vendors as originally stated on the quotation document.
- 3.6. The bidder must ensure the correctness & validity of the quotation:
  - (i) that the price(s), rate(s) & preference quoted cover all for the work/item (s) & accept that any mistakes regarding the price (s) & calculations will be at the bidder's risk
  - (ii) it is the responsibility of the bidder to confirm receipt of their quotation and to keep proof thereof.
- 3.7. The bidder must accept full responsibility for the proper execution & fulfilment of all obligations conditions devolving on under this agreement, as the Principal (s) liable for the due fulfilment of this contract.
- 3.8. This quotation will be evaluated based on the 80/20 points system, specification, correctness of information and/or functionality criteria. All required documentation must be completed in full and submitted.
- 3.9. Offers must comply strictly with the specification.
- 3.10. Only offers that meet or are greater than the specification will be considered.
- 3.11. Late offers will not be considered.
- 3.12. Expired product/s will not be accepted. All products supplied must be valid for a minimum period of six months.
- 3.13. Used/ second-hand products will not be accepted.
- 3.14. A bidder not registered on the Central Suppliers Database or whose verification has failed will not be considered.
- 3.15. All delivery costs must be included in the quoted price for delivery at the prescribed destination.
- 3.16. Only firm prices will be accepted. Such prices must remain firm for the contract period. Non-firm prices (including rates of exchange variations) will not be considered.
- 3.17. In cases where different delivery points influence the pricing, a separate pricing schedule must be submitted for each delivery point.
- 3.18. In the event of a bidder having multiple quotes, only the cheapest according to specification will be considered.
- Verification will be conducted to identify if bidders have multiple companies and are cover-quoting for this bid.
- 3.20. In such instances, the Department reserves the right to immediately disqualify such bidders as cover-quoting is an offence that represents both corruption and acquisition fraud.

# 4. SPECIAL INSTRUCTIONS AND NOTICES TO BIDDERS REGARDING THE COMPLETION OF THIS QUOTATION.

- 4.1. Unless inconsistent with or expressly indicated otherwise by the context, the singular shall include the plural and vice versa and with words importing the masculine gender shall include the feminine and the neuter.
- 4.2. Under no circumstances whatsoever may the quotation/bid forms be retyped or redrafted. Photocopies of the original bid documentation may be used, but an original signature must appear on such photocopies.
- 4.3. The bidder is advised to check the number of pages and to satisfy himself that none are missing or duplicated.
- 4.4. Quotations submitted must be complete in all respects. However, where it is identified that information in a bidder's response, which does not affect the preference points or price, is incomplete in any respect, the said supplier meets all specification requirements and scores the highest points in terms of preference points and price, the Department reserves the right to request the bidder to complete/submit such information.
- 4.5. Any alteration made by the bidder must be initialled; failure to do so may render the response invalid.
- 4.6. Use of correcting fluid is prohibited and may render the response invalid.
- 4.7. Quotations will be opened in public as soon as practicable after the closing time of quotation.
- 4.8. Where practical, prices are made public at the time of opening quotations.
- 4.9. If it is desired to make more than one offer against any individual item, such offers should be given on a photocopy of the page in question. Clear indication thereof must be stated on the schedules attached.

4.10. The Department is under no obligation to pay suppliers in part for work done if the supplier can no longer for fulfil their obligation.

# 5. SPECIAL INSTRUCTIONS REGARDING HAND DELIVERED QUOTATIONS

- 5.1. Quotation shall be lodged at the address indicated not later than the closing time specified for their receipt, and in accordance with the directives in the quotation documents.
- 5.2. Each quotation shall be addressed in accordance with the directives in the quotation documents and shall be lodged in a separate sealed envelope, with the name and address of the bidder, the quotation number and closing date indicated on the envelope. The envelope shall not contain documents relating to any quotation other than that shown on the envelope. If this provision is not complied with, such quotations/bids may be rejected as being invalid.
- 5.3. All quotations received in sealed envelopes with the relevant quotation numbers on the envelopes are kept unopened in safe custody until the closing time of the quotation/bids. Where, however, a quotation is received open, it shall be sealed. If it is received without a quotation/bid number on the envelope, it shall be opened, the quotation number ascertained, the envelope sealed and the quotation number written on the envelope.
- 5.4. A specific box is provided for the receipt of quotations, and no quotation found in any other box or elsewhere subsequent to the closing date and time of quotation will be considered.
- 5.5. No quotation/bid sent through the post will be considered if it is received after the closing date and time stipulated in the quotation documentation, and proof of posting will not be accepted as proof of delivery.
- 5.6. Quotation documents must not be included in packages containing samples. Such quotations may be rejected as being invalid.

#### 6. SAMPLES

(i)

- 6.1. In the case of the quote document stipulating that samples are required, the supplier will be informed in due course when samples should be provided to the institution. (This decreases the time of safety and storage risk that may be incurred by the respective institution). The bidders sample will be retained if such bidder wins the contract.
- (i) If a company/s who has not won the quote requires their samples, they must advise the institution in writing of such.
- (ii) If samples are not collected within three months of close of quote the institution reserves the right to dispose of them at their discretion.
- 6.2. Samples must be made available when requested in writing or if stipulated on the document.
- (i) If a Bidder fails to provide a sample of their product on offer for scrutiny against the set specification when requested, their offer will be rejected. All testing will be for the account of the bidder.

take place

# 7. COMPULSORY SITE INSPECTION / BRIEFING SESSION

The institution has determined that a compulsory site meeting

7.1. Bidders who fail to attend the compulsory meeting will be disqualified from the evaluation process.

(ii) Date <u>08 /09 /2022</u> Time <u>10:30; am</u> Place <u>MPUMEL</u>	ELO CLINIC
Institution Stamp:	Institution Site Inspection / briefing session Official
	Full Name:
	Signature:
	Date:

### 8. STATEMENT OF SUPPLIES AND SERVICES

8.1. The contractor shall, when requested to do so, furnish particulars of supplies delivered or services executed. If he/she fails to do so, the Department may, without prejudice to any other rights which it may have, institute inquiries at the expense of the contractor to obtain the required particulars.

### 9. SUBMISSION AND COMPLETION OF SBD 6,1

9.1. Should a bidder wish to qualify for preference points they must complete a SBD 6.1 document. Failure by a bidder to provide all relevant information required, will result in such a bidder not being considered for preference point's allocation. The preferences applicable on the closing date will be utilized. Any changes after the closing date will not be considered for that particular quote.

### 10. TAX COMPLIANCE REQUIREMENTS

- 10.1. In the event that the tax compliance status has failed on CSD, it is the suppliers' responsibility to provide a SARS pin in order for the institution to validate the tax compliance status of the supplier.
- 10.2. In the event that the institution cannot validate the suppliers tax clearance on SARS as well as the Central Suppliers Database, the quote will not be considered and passed over as non-compliant according to National Treasury Instruction Note 4 (a) 2016/17.

### 11. TAX INVOICE

- 11.1. A tax invoice shall be in the currency of the Republic of South Africa and shall contain the following particulars:
- (i) the name, address and registration number of the supplier;
- (ii) the name and address of the recipient;
- (iii) an individual serialized number and the date upon which the tax invoice is issued;
- (iv) a description and quantity or volume of the goods or services supplied;
- (v) the official department order number issued to the supplier;
- (vi) the value of the supply, the amount of tax charged;
- (vii) the words tax invoice in a prominent place.

#### 12. PATENT RIGHTS

The supplier shall indemnify the KZN Department of Health (hereafter known as the purchaser) against all third-party claims of infringement of patent, trademark, or industrial design rights arising from use of the goods or any part thereof by the purchaser.

# 13. PENALTIES

- 13.1. If at any time during the contract period, the service provider is unable to perform in a timely manner, the service provider must notify the institution in writing/email of the cause of and the duration of the delay. Upon receipt of the notification, the institution should evaluate the circumstances and, if deemed necessary, the institution may extend the service provider's time for performance.
- 13.2. In the event of delayed performance that extends beyond the delivery period, the institution is entitled to purchase commodities of a similar quantity and quality as a substitution for the outstanding commodities, without terminating the contract, as well as return commodities delivered at a later stage at the service provider's expense.
- 13.3. Alternatively, the institution may elect to terminate the contract and procure the necessary commodities in order to complete the contract. In the event that the contract is terminated the institution may claim damages from the service provider in the form of a penalty. The service provider's performance should be captured on the service provider database in order to determine whether or not the service provider should be awarded any contracts in the future.
- 13.4. If the supplier fails to deliver any or all of the goods or to perform the services within the period(s) specified in the contract, the purchaser shall, without prejudice to its other remedies under the contract, deduct from the contract price, as a penalty, a sum calculated on the delivered price of the delayed goods or unperformed services using the current prime interest rate calculated for each day of the delay until actual delivery or performance.

### 14. TERMINATION FOR DEFAULT

- 14.1. The purchaser, without prejudice to any other remedy for breach of contract, by written notice of default sent to the supplier, may terminate this contract in whole or in part:
  - (i) if the supplier fails to deliver any or all of the goods within the period(s) specified in the contract,
- (ii) If the supplier fails to perform any other obligation(s) under the contract; or
- (iii) if the supplier, in the judgment of the purchaser, has engaged in corrupt or fraudulent practices in competing for or in executing the contract.
- 14.2. In the event the purchaser terminates the contract in whole or in part, the purchaser may procure, upon such terms and in such manner as it deems appropriate, goods, works or services similar to those undelivered, and the supplier shall be liable to the purchaser for any excess costs for such similar goods, works or services.
- 14.3. Where the purchaser terminates the contract in whole or in part, the purchaser may decide to impose a restriction penalty on the supplier by prohibiting such supplier from doing business with the public sector for a period not exceeding 10 years.

# 15. THE DEPARTMENT RESERVES THE RIGHT TO PASS OVER ANY QUOTATION WHICH FAILS TO COMPLY WITH THE ABOVE.

# PREFERENCE POINTS CLAIM FORM IN TERMS OF THE PREFERENTIAL PROCUREMENT REGULATIONS 2017

This preference form must form part of all quotes invited. It contains general information and serves as a claim form for preference points for Broad-Based Black Economic Empowerment (B-BBEE) Status Level of Contribution

NB: BEFORE COMPLETING THIS FORM, BIDDERS MUST STUDY THE GENERAL CONDITIONS, DEFINITIONS AND DIRECTIVES APPLICABLE IN RESPECT OF B-BBEE, AS PRESCRIBED IN THE PREFERENTIAL PROCUREMENT REGULATIONS, 2017.

## 1. GENERAL CONDITIONS

- 1.1 The following preference point systems are applicable to all quotes:
  - the 80/20 system for requirements with a Rand value of up to R50 000 000 (all applicable taxes included); and
- 1.2 The value of this quote is estimated to not exceed R50 000 000 (all applicable taxes included) and therefore the 80/20 preference point system shall be applicable.
- 1.3 Points for this quote shall be awarded for:
  - (a) Price; and
  - (b) B-BBEE Status Level of Contributor.
- 1.4 The maximum points for this quote is allocated as follows:

	POINTS
PRICE	80
B-BBEE STATUS LEVEL OF CONTRIBUTOR	20
Total points for Price and B-BBEE must not exceed	100

- Failure on the part of a bidder to submit proof of B-BBEE Status level of contributor together with the quote, will be interpreted to mean that preference points for B-BBEE status level of contribution are not claimed.
- 1.6 The purchaser reserves the right to require of a bidder, either before a quote is adjudicated or at any time subsequently, to substantiate any claim in regard to preferences, in any manner required by the purchaser.

### 2. DEFINITIONS

- (a) "B-BBEE" means broad-based black economic empowerment as defined in section 1 of the Broad-Based Black Economic Empowerment Act;
- (b) "B-BBEE status level of contributor" means the B-BBEE status of an entity in terms of a code of good practice on black economic empowerment, issued in terms of section 9(1) of the Broad-Based Black Economic Empowerment Act;
- (c) "bid" means a written offer in a prescribed or stipulated form in response to an invitation by an organ of state for the provision of goods or services, through price quotations, advertised competitive bidding processes or proposals;
- (d) "Broad-Based Black Economic Empowerment Act" means the Broad-Based Black Economic Empowerment Act, 2003 (Act No. 53 of 2003);
- (e) "EME" means an Exempted Micro Enterprise in terms of a code of good practice on black economic empowerment issued in terms of section 9 (1) of the Broad-Based Black Economic Empowerment Act;
- (f) "functionality" means the ability of a tenderer to provide goods or services in accordance with specifications as set out in the tender documents.
- (g) "prices" includes all applicable taxes less all unconditional discounts;
- (h) "proof of B-BBEE status level of contributor" means:
  - B-BBEE Status level certificate issued by an authorized body or person;
  - A sworn affidavit as prescribed by the B-BBEE Codes of Good Practice;
  - Any other requirement prescribed in terms of the B-BBEE Act;
- (i) "QSE" means a qualifying small business enterprise in terms of a code of good practice on black economic empowerment issued in terms of section 9 (1) of the Broad-Based Black Economic Empowerment Act;
- (j) "rand value" means the total estimated value of a contract in Rand, calculated at the time of bid invitation, and includes all applicable taxes;

# 3. POINTS AWARDED FOR PRICE

# 3.1 THE 80/20 PREFERENCE POINT SYSTEMS

A maximum of 80 points is allocated for price on the following basis:

$$Ps = 80 \left( 1 - \frac{Pt - P\min}{P\min} \right)$$
 Where

Ps

Points scored for price of bid under consideration

Pt Pmin

Price of bid under consideration price of lowest acceptable bid

# 4. POINTS AWARDED FOR B-BBEE STATUS LEVEL OF CONTRIBUTOR

4.1 In terms of Regulation 6 (2) and 7 (2) of the Preferential Procurement Regulations, preference points must be awarded to a bidder for attaining the B-BBEE status level of contribution in accordance with the table below:

-BBEE Status Level of Contributo	Number of points (80/20 system)
1	20
2	18
3	14
4	12
5	8
6	6
7	4
8	2
Non-compliant contributor	0

5.	DID	DECL	ABAR	
IJ.	101113	$\mathbf{D} = \mathbf{U}$	AKAI	HE SIM

5.1 Bidders who claim points in respect of B-BBEE Status Level of Contribution must complete the following:

# 6. B-BBEE STATUS LEVEL OF CONTRIBUTOR CLAIMED IN TERMS OF PARAGRAPHS 1.4 AND 4.1

6.1	B-BBEE Status Level of Contributor:	=	(maximum of 20 points)
-----	-------------------------------------	---	------------------------

(Points claimed in respect of paragraph 7.1 must be in accordance with the table reflected in paragraph 4.1 and must be substantiated by relevant proof of B-BBEE status level of contributor.

7.	SUB-CONTRACTING applicable box)
7.1	Will any portion of the contract be sub-contracted?

YES NO

7.1.1 If yes, indicate:

iii) The B-BBEE status level of the sub-contractor.....

8. Whether the sub-contractor is an EME or QSE

(Tick applicable box)

(Tick

Specify, by ticking the appropriate box, if subcontracting with an enterprise in terms of Preferential Procurement Regulations,2017:

Designated Group: An EME or QSE which is at last 51% owned by:

EME

QSE

Designated Group: An EME or QSE which is at last 51% owned by:	EME	QSE
Black people	<u>v</u>	- V
Black people who are youth		
Black people who are women		+
Black people with disabilities		
Black people living in rural or underdeveloped areas or townships		
Cooperative owned by black people		
Black people who are military veterans		
OR OR		
Any EME		
Any QSE		

9.	DECLA	RATION WITH REGARD TO COMPANY/FIRM	
9.1	Name	e of company/firm:	
9.2		registration number:	
9.3		pany registration number:	
9.4		OF COMPANY/ FIRM [TICK APPLICABLE BOX	
		Partnership/Joint Venture / Consortium One person business/sole propriety Close corporation Company (Pty) Limited	
9.5		CRIBE PRINCIPAL BUSINESS ACTIVITIES	
9.6	COM	PANY CLASSIFICATION [TICK APPLICABLE BC	
		Manufacturer Supplier Professional service provider Other service providers, e.g. transporter, etc.	
9.7	Total r	number of years the company/firm has been in bu	siness:
9.8	I/we, t the B-	he undersigned, who is / are duly authorised to d	o so on behalf of the company/firm, certify that the points claimed, based or raphs 1.4 and 6.1 of the foregoing certificate, qualifies the company/ firm for
	i) T	he information furnished is true and correct;	
	ii) T	he preference points claimed are in accordance v	vith the General Conditions as indicated in paragraph 1 of this form;
	iii) lr b	n the event of a contract being awarded as a resu e required to furnish documentary proof to the sa	llt of points claimed as shown in paragraphs 1.4 and 6.1, the contractor may tisfaction of the purchaser that the claims are correct;
	iv) If	the B-BBEE status level of contributor has be ontract have not been fulfilled, the purchaser may	en claimed or obtained on a fraudulant basis or any of the
	(a)	disqualify the person from the bidding process;	
	(b)		ed or suffered as a result of that person's conduct;
	(c)		nich it has suffered as a result of having to make less favourable
	(d)	mio dottod on a maudulent pasis, pe resincien	nareholders and directors, or only the shareholders and directors by the National Treasury from obtaining business from any organ ofter the audi alteram partem (hear the other side) rule has been
	(e)	forward the matter for criminal prosecution.	
	WITNI	ESSES	
			SIGNATURE(S) OF BIDDERS(S)
	1		DATE:
	2		ADDRESS
	L		



Institution name:			

# COMPLAINTS PROCESS FOR QUOTATIONS R2 000.00 TO R500 000.00 INCLUDING V.A.T

# 1. Supplier Submits Written Complaint / Objection

- Bidders aggrieved by decisions or actions taken by the Department or Institution during the SCM procurement process, must lodge a written complaint immediately.
- > Complaints lodged two (2) or more days after the award will not be entertained.
- > Complaints must be directed to the Responsibility Manager of the institution (Hospital or CHC) and District Finance Manager for District Offices.
- > It must be noted that this is not an appeals process and as such will not halt the procurement process.

# 2. Institution Prepares Written Response to Complaint

- > The Responsibility Manager, or his appointee, must prepare a response letter to the complainant.
- > The complaint must be resolved within 60 days.
- Should the complainant not be satisfied with the response, the matter will be referred to the District Finance Manager (applicable to all Hospitals and CHC) or District Manager (Applicable to all District Offices) for a final verdict.
- > Should the complainant still not be satisfied with the response received, they may then seek legal recourse at their own expense.

Complaints or objections should	l be directed to:
Responsibility Manager:	
Email Address:	

# PROVINCE OF KWAZULU-NATAL DEPARTMENT OF HEALTH

#### ZNQ -

# **MPUMELELO CLINIC - ALTERATIONS TO ACCOMMODATE RECEPTION**

### 3. SCOPE OF WORK

The work to be carried out under this contract includes the supply of all materials, and including all labour to carry out all electrical work and leaving in service condition to the satisfaction of the Secretary for Health: KwaZulu-Natal.

- 3.1. The work comprises of
- 3. 2 Supply and install the following
  - a) Alterations removal of the vinyl floor tiles

#### **METALWORK**

**PROPRIETARY MATERIALS:** — Where proprietary materials are specified, the materials used are to be of the type, specified or other approved by the Department.

RATES: — for all metalwork, unless otherwise stated, are to include for cutting to length, shaping, turning, threading, forging, fitting, assembling, riveting, welding, welded running joints, filing smooth, also for all screws and holes and hoisting and fixing in position. All screwed work is to have full threads

**ALUMINIUM AND ANODISED ALUMINIUM:** — is to be of the brand specified or other approved and of 6063-TF or equivalent quality and temper.

Aluminium bars and sections shall comply with the relevant clauses of SANS 1476, extruded tube and hollow sections with the relevant clauses of SANS 1474, and sheet and strips with the relevant clauses of SANS 1470. All alloys to be anodised are to be of anodising quality.

Aluminium is to be free from flaws, hammer and die markings or other imperfections. Anodising of aluminium is to be carried out in accordance with SANS Specification 999 by an approved process. The average anodic film thickness shall be 25 micrometer, and at no point should the anodic film thickness fall below 22 micrometer or be thicker than 30 micrometer.

to anodising, all surfaces are to be de-greased and cleaned, all irregularities removed and flushed off smooth and buffed where necessary.

All anodised aluminium must be coated with a suitable "non-yellowing" methylcrylate lacquer film, approved by the Department, over the entire surface. The lacquer film must be continuous and of a uniform average thickness not less than 10 micrometer. The lacquer thickness must be determined by use of a film meter or other instrument methods as described in ASTM B244-49T. Rates for anodised aluminium must include for this protective coating.

Before the work is put in hand, samples of finish are to be submitted to the Department for approval, and all finished work is to be equal in all respects to the approved samples.

The Contractor shall provide all samples required for testing in accordance with SANS Specification 999. If required, tests on the anodic film are to be carried out at the works of the anodised to verify that the work conforms to SANS Specification 999, the cost of which will be borne by the Contractor.

The surfaces of all aluminium which are jointed to or are in contact with other materials when fixed, particularly ferrous metals, are to be suitably insulated to prevent electrolytic corrosion.

Joints in all aluminium members are to be neatly formed in an approved manner with screw heads, pins, rivets, etc. concealed so that the joints are practically invisible. Screw or bolt jointing is to be kept to a minimum and will be permitted only when welding is impracticable.

Unless otherwise described, stainless steel screws or bolts are to be used for jointing and fixing aluminium work. Welded joints are to be formed by argon arc process using SANS 1476/NS6 welding rods and finished off smooth.

Welding is to be executed in such a manner as not to affect the colour of the material or the anodic coating.

Exposed heads of screws, pins, rivets, etc. in coloured anodised aluminium are to be touched up with enamel paint to match the coloured anodised finish.

in the general construction and design affecting neatness, strength or durability may be introduced. If any deviation is proposed, the Contractor must submit detailed drawings showing the particular construction and form or section he proposes to use and such drawings, details and samples of fittings, etc. are to be approved by the Department before manufacture is commenced and every facility must be given for the work to be inspected during manufacture.

No work may be fixed in position until it has been inspected and approved. Anodised aluminium work must be erected as near to the end of the Contract period as possible, to minimise the danger of damage or deterioration.

All work is to be suitably protected during building operations and left in a clean and satisfactorily finished condition on completion. In particular, all anodised aluminium work must be protected against damage, and against deterioration or discolouration caused by mortar droppings, wax, paint, etc. all to the entire satisfaction of the Department. All work so damaged, deteriorated or discoloured must be replaced at the Contractor's expense.

Rates for aluminium work are to include for necessary cutting to lengths, shaping, turning, threading, forging, fitting, assembling, riveting, welding, welded running joints, filing smooth, also for all screws and holes and hoisting and fixing in position. All screwed work is to have full threads.

**ANODISED ALUMINIUM WELDED WINDOWS AND DOORS**: — are to be of an approved manufacture and design.

Windows and doors are to be fabricated from Medium Universal equal leg sections, unless otherwise specified, measuring 33mm over one opening section and not less than 4mm thick through the flanges and not less than 4.75mm through the web, unless otherwise stated.

The aluminium sections are to be of approved manufacture and of 6063-TF or equivalent quality and temper and are to be anodised after manufacture to the approval of the Department. Welds are to be electrically flash butt resistance welded, properly ground and cleaned off to give a uniform appearances.

Anodising, etc. is to be carried out as before described.

windows and doors are to be suitable for internal glazing and are to be fitted with approved anodised aluminium glazing beads of the "clip on" type. Drilling for the fixing of glazing beads is to be done to suit the thickness of the glass used.

The frames are to be perfectly flat, square, butt-welded at joints (mechanical joints will not be permitted) and all opening sashes must fit perfectly on all faces and open or close freely without binding at any point. The glazing bars must be continuous with continuous intersections (mitred intersections will not be permitted) with ends scribed and fitted to the frames with shouldered ends passed through and riveted over. The sight lines of the main frame, whether consisting of all fixed lights, all opening sashes or portions of both and the glass plane must be the same throughout each window.

Weathering on sections is to be solid extruded with the sections (screwed or riveted on strips will not be permitted) except weather bars to sills of inward opening sashes which must be welded on and not screwed or riveted except in the approved designs of built-up transoms.

No steel is to be used in the manufacture of the windows unless it is stainless steel of quality to A.I.S.I. Type 316. All fittings, butt hinges, screws, nuts, bolts, etc. are to be of high quality aluminium or other approved non-corrosive material compatible with aluminium and of sufficient strength to perform the functions for which they are used. The handles, sliding stays and peg stays are to have nylon washers, bushes and pressure pads and are to be secured to the frames with screws having riveted ends. Pop rivet fixings will not be permitted.

The transoms and mullions of all purpose-made windows and doors are to be equally spaced between the outer frames to form openings of equal size. Where this is not the case, either the width or the height of the opening is stated. Unless otherwise stated, the fixed lights and sashes of all purpose-made windows and doors are to be in one square and the sashes and doors are to open out.

Frames must be provided with suitable fixing lugs bolted on to frame with aluminium alloy bolts or are to be holed for screwing as required with lugs or holes spaced one near top, one near bottom and not more than 750mm apart intermediately each side of frame.

Frames more than 900mm wide are to be provided with similar fixings to top and bottom and not more than 750mm apart.

All composite windows, doors, etc. are to be supplied with suitable and approved coupling mullions or transoms. Rectangular hollow section transoms where specified are to be

25mm x 115mm in section manufactured from 3mm thick aluminium.

The Contractor must submit drawings showing details of sections he proposes to use and

these drawings are to be approved by the Department before manufacture is commenced, and when requested, specimen windows and doors complete with all fittings as well as specimen coupling mullions, transoms etc. must be submitted for approval and all windows, doors, etc. supplied must conform to the approved samples.

manufacturer of the windows and doors must supply a dimensioned set of drawings with the windows and doors, for use on the site, including clearance and strict fixing methods and details.

Windows and doors are to be delivered to the site in suitable protective wrappings or crates and are to be stacked on end and carefully handled at all times to prevent any marking or staining of surfaces.

Immediately the windows and doors have been delivered on the site, they are to be thoroughly overhauled and all necessary adjustments or repairs are to be made before they are fixed in position. A further inspection is to be made after fixing and any further servicing required must be carried out in order to leave the windows and doors in a satisfactory condition and waterproof after glazing is completed.

**Side Hung Sashes**: — are to open out on a pair of aluminium hinges complete with antifriction weatherproof bushings fixed pin and nylon washers and fitted with anodised aluminium alloy sliding stay with friction fastener and an approved anodised aluminium two point handle and striking plate.

Bottom Hung Sashes: — are to open in on a pair of aluminium hinges complete with antifriction weatherproof bushings, fixed pin and nylon washers and fitted with concealed side arms and strong lever action spring catch and keep.

**Top Hung Sashes**: — are to open out on a pair of aluminium hinges complete with antifriction weather proof bushings, fixed pin and nylon washers and fitted with anodised aluminium peg stay with cranked locking stay.

**Pivot Hung Sashes**: — are to be hung on a pair of approved weatherproof brass satin-chrome finished friction pivots of the greatest possible diameter permissible and fitted at top with strong lever action spring catch for long arm or hand operation and striking plate, unless otherwise stated.

**Vertically Pivot Hung Sashes**: — are to be hung on free pivot cups at the head incorporating nylon bearing sleeves and lever pivots at the sill and fitted with one two-point casement handle and striking plate.

**Projected Out Sashes**: — are to be balanced on approved concealed side arms with stainless steel shoes and channels and fitted at bottom with one approved bow handle with catch incorporated.

In Sashes: — are to be balanced on approved concealed side arms with stainless steel shoes and channels and fitted at top with strong lever action spring catch for long arm or band operation and striking plate:

**Doors:** — are to be side hung to open out on one and a half pairs of aluminium hinges to each leaf complete with anti-friction weatherproof bushings, fixed pin and nylon washers and fitted with lock set as specified, and each lock is to be provided with two keys. Satin chrome finish flush bolts are to be fitted at top and bottom of meeting edge of first closing leaf of double doors.

Adjustable Louver Sets: — are to be approved anodised aluminium adjustable louver sets consisting of head and all weather strips fitted with neoprene gaskets and two jamb strips

each fitted with louver brackets with spring loaded clips for the specified width of glass louver blades and complete with tilt bars and operating lever handles. Where the openings are not of height to suit standard width louver blades an alternate head section with static clips must be provided to take a fixed louver blade of the required width. The sets-sets are to be tap screwed to the window frame with stainless steel self-tapping screws.

# **GLAZING TO DOORS / ALUMINIUM GLAZED SCREENS**

No glazing permitted to any fitting below Lock Rail (ie 1,2m high.).

**Burglar Bars**: — are to be standard type burglar bars formed of 20mm x 5mm aluminium bars riveted at intersections and riveted at ends to the window frame with high strength aluminium rivets. The burglar bars to the small pane type window are to line through with the glazing bars, and windows of the horizontal-pane type or of the no-glazing bar type are to be fitted with burglar bars which are divided as for the small pane type window.

All exposed surfaces of anodised aluminium are to be protected by means of an approved fabric backed adhesive tape. The Contractor shall satisfy the Department that the tape he proposes to use can be easily stripped after long exposure to sunlight, and rates are to include or the final stripping of the protective tape and cleaning dawn to approval at completion.

All work is to be protected during building against deterioration or discolouration caused by mortar droppings, wax, paint, etc. and all work so damaged is to be replaced at the Contractor's expense to the approval of the Department.

All glass and glazing has been elsewhere measured. All sashes and openings, unless otherwise stated, are to be single panes without glazing bars.

All windows and doors must be fixed into preformed openings in the structure (the buildingin of windows and doors will not be pen fitted) and rates are to include for supplying necessary templates for forming the openings. Fixing in position of windows and doors has been measured separately. Sizes of windows and doors are given to the nearest 10mm.

ADJUSTABLE LOUVER GEAR SETS: — are to be approved natural anodised aluminium adjustable sets consisting of head and sill weather strips fitted with neoprene gaskets and two jamb strips and fitted with sets brackets with spring loaded clips for the specified glass sets blades and complete with tilt bars and operating handles. Where the openings are not of a height to suit standard width sets blades an alternate head section with static clips must be provided to take a fixed sets blade of the required width.

**RATES**: — are to include for fixing in accordance with the manufacturers instructions for screwing head and sill weather strips and jamb strips with stainless steel screws to frames (Elsewhere measured) and for oiling and easing at completion.

# DEMOUNTABLE PARTITIONS 50MM (NATURAL ANODISED).

# **Extruded Aluminium Sections**

Supply and fit demountable "Kappa" partition system comprising anodized aluminium UChannel fitted to suspended ceilings. Vertical split-post (mullion) to be fitted between floor and ceiling U-Channel at 1225mm c/c with angle brackets. Once framing is fixed, fit panels into place and secure with clip-on cover plates.

All aluminium sections may be anodized or powder coated in a variety of colours.

# **Panels**

41mm thick semi solid core panels 2032 x 1200mm. The panels are made up of two outer skins of 3.2mm hardboard cladding. Lower panels to be provided with a 150mm wide solid mid-rail 850mm from the base of the panel to the centre of the mid-rail built in as part of the construction. The panels to be prepared before applying the final finish as specified.

### Construction

Right angled corners to be formed with natural anodized aluminium radiused corner post fitted from floor to ceiling. Floor fixing to be angle brackets and ceiling fixing to be hidden block. The ceiling U-Channel butts up against radiused corner post.

### **Door Frames**

Door frames to be natural anodized aluminium pre-fitted with woolpile gaskets, clipped into H-Profile at head and clipped into combination split post and cover plate at styles. The rebate on the door frame caters for standard doors of a thickness between 40mm and 44mm.

### Glazing

Glazed panes to be framed with H-Profile fitted horizontally at top and bottom, butted against side of split-post and clip on cover plate combination and fixed with angle brackets. Glazing sections pre-fitted with woolpile gaskets and set into H-profiles and into post / cover plate combinations to form a neat glazing opening. Glazing beads pre-fitted with woolpile gaskets and then clipped into glazing section.

### **Termination**

Openings for louver frames, sliding doors and windows, serving hatches and partition ends are to be lined with the aluminium termination section.

# **Skirtings**

76mm high aluminium skirting to be glued to panels.

#### PAINTING

**MATERIALS**: — Proprietary materials where specified are to be of the brand specified or other approved by the Department.

All primers, emulsion paints, enamels, stains, varnishes, etc. are to comply with the relevant SANS Specification.

Paints, etc. shall be suitable for application on the surfaces to which they are being applied and those used externally shall be of exterior quality or suitable for exterior use. For any particular work the priming coat and subsequent coats of paint are to be executed with paints from the same manufacturer and in accordance with that manufacturer's instructions.

The materials are to be brought to the site in unopened containers and no adulteration will be permitted, except thinners of a quantity and quality directed by the manufacturer. The Department shall at all times be permitted to take samples for testing purposes from open containers of any brand of paint being used on the work.

All materials, if and when required by the Department, will be subject to tests by the South African Bureau of Standards, and the cost of such tests, should the material under test not meet the requirements of this specification, shall be borne by the Contractor. Fillers and stoppings are to be suitable for use with the material being filled or stopped and to the approval of the Department.

PREPARATORY WORK: — All new and existing surfaces are to be thoroughly dry and are to be cleaned of all dust, dirt, grease, oil, rust, scale, efflorescence, fungus, loose or flaking material, etc. rubbed down, stopped, filled, knotted and sanded smooth as required in

accordance with the paint manufacturer's recommendations and to the approval of the Department prior to the application of paint, etc.

Ceilings are to have nail heads, including those to cornices and cover strips, primed and stopped up as necessary and rubbed down smooth.

Asbestos cement shall be primed with an approved alkali resistant primer before the application of subsequent coats which are not, in themselves, alkali resistant. Iron, steel and other ferrous metals shall be cleaned in accordance with SANS Code of

Practice 064 to remove rust, scale, grease, oil, etc. and the surface brought to a bright metallic condition.

Galvanized iron and zinc shall be cleaned in accordance with SANS Code of Practice 062 to remove the manufacturer's temporary protective coating, white rust, etc. Other non-ferrous metals shall be thoroughly cleaned to remove all milling oils, temporary protective coatings, etc. and the surface abraded with fine water-paper and white spirit. Woodwork to be painted shall have all knots and resinous areas treated with an approved knotting, the surface shall then be primed and all holes, etc. stopped and rubbed down smooth,

Woodwork to be oiled, stained, varnished, etc. shall be free of all stains, pencil marks and other surface discolorations and all holes, etc. stopped with tinted stopping and rubbed down smooth.

In preparing existing glazed sashes and sash doors, all loose putty is to be removed, the rebates primed and glass re-sprigged and re-puttied as necessary before the painting is commenced.

Previously distempered or lime washed surfaces to receive any other type of paint, are to have the existing distemper or lime wash completely removed by scraping or wire brushing and the surfaces treated with an approved bonding liquid.

Where existing paint film are in good condition any flaking or bared patches are to be properly feathered into the surrounding paint and spot primed as necessary.

Where existing paint films are in poor condition and require to be removed completely, they are to be removed by means of wire brushing, paint remover, burning off, or other approved method. Paint removers shall be free of wax and caustic substances and shall preferably be of water rinseable type. When burning off paint from wood, care must be taken to avoid charring the wood.

The final state of preparatory work to existing decorated surfaces shall in all cases produce in the finished decorated surfaces a condition similar to new work.

The Contractor will be held responsible for the proper and adequate preparation of the surfaces and any work which fails to meet the manufacturer's recommendations must be made good at the Contractor's expense to the satisfaction of the Department.

**APPLICATION OF PAINTS, ETC.:** — Painting may be carried out by brush, roller or spray as recommended by the manufacturer and to the approval of the Department. All paints, etc. are to be applied in strict accordance with the manufacturer's instructions. Each coat of paint is to be adequately and permanently keyed onto the previous coat or surface and shall be evenly distributed and continuous and shall dry to a smooth film, free from sags, runs or other imperfections. Each coat of paint is to be of a colour distinctive from previous or succeeding coats.

All painting must be done in accordance with a colour scheme which will be provided by the Department, and rates for painting etc. are to include for all cutting in of contrasting colours and masking as required. No distinction has been made where more than one colour of the

same material is required on the walls or ceiling of the same room.

Samples of colours for the final coats are to be prepared in all cases to the approval of the Department and all work must be finished to the approved colours. Backs of wood door and similar frames an the surfaces of other new or prefixed joinery in contact with brickwork, etc. and built in as the work proceeds, shall be primed or sealed before building in to prevent moisture seeping into the wood from the mortar bedding.

Tongued and grooved and rebated edges of boards in batten doors and other such like inaccessible parts of new joinery shall, before assembly, be primed, or where the joinery is to receive a finish other than paint, be given one coat of such other finishing material.

All new external structural timbers shall be primed before the timbers are fixed in position and shall include all surfaces such as backs of fascias and barge boards.

RATES: — Rates for painting, etc. are to include for all preparatory work, and where spraying is employed, are to include or adequately masking all surrounding areas. Where diameters of pipes are stated these are the nominal internal diameters, and rates for painting pipes are to include for painting the holderbats, hangers, clips, etc. supporting the pipes.

Rates are to include for providing all necessary dust sheets, covers, etc. taking all necessary precautions to prevent marking the surfaces of joinery, walls, floors, glass, electrical fittings, etc. All surfaces disfigured or otherwise damaged shall be completely renovated or replaced as necessary to the approval of the Department at the Contractor's own expense.

# PROVINCE OF KWAZULU-NATAL DEPARTMENT OF HEALTH

ZNQ -

# MPUMELELO CLINIC- ALTERATIONS TO ACCOMMODATE RECEPTION

#### SCHEDULE OF RATES

### 4.1 ITEMS AND PRICING

The Department reserves the right to place an order for any quantities of items included in the Schedules. The Schedule of Rates must also not be assumed to include and describe every detail of the supply requirement, but must be taken and read in conjunction with the other parts of the document. Thus the supplier shall not have claim for further payment in respect of any order which may be described or implied in the contract, although apparently no corresponding items are given in the Schedule of Rates. The supplier shall be deemed to have satisfied himself before quoting as to the correctness and sufficiency of his quote for the contract and of the rates and prices stated in the Schedule of Rates.

### 4.2 TAX AND DUTIES

Prices, quoted and paid, must include all customs, excise and import duties, and any other tariffs or taxes levied by the government or statutory body having jurisdiction on the goods provided under this contract, including Value Added Tax (applicable to the current rate).

### 3.3 RATES

Except where provision is made in the Schedule of Rates, the rates and prices inserted shall be the full rates and prices for the service delivered described under the respective items and shall cover all labour, transport, overhead charges and profit, etc. as well as the general liabilities, obligations and risks arising out of the Conditions of Contract, the overhead charges and profit being spread proportionately over the rates of the relative items in the Schedule of Rates.

ltem No	Description	Qty	Rate	Amount
-	BILL NO. 1			
	CARPENTRY AND JOINERY			
	PREAMBLES			
	For Preambles refer to "Standard Preambles to all trades - WB20 - 1986"			
	SUPPLEMENTARY PREAMBLES			
	TIMBER			
	All softwood to be South African pine. All hardwood to be Iroko unless otherwise specified.			
	DESCRIPTIONS			
	The term "planted on" shall mean the nailing of one timber member to another.			
	The term "screwed on" shall mean the countersunk screwing of one timber member to another.			
	The term "screwed on and pelleted" shall mean the screwing of one timber member to another with the heads of screws sunkand pelleted.			
-	The term "plugged" shall mean the countersunk screwing of a timber member to and including plastic plugs in brickwork or			
	The term "plugged and pelleted" shall mean the screwing of a timber member to and including plastic plugs in brickwork or concrete with heads of screws sunk and pelleted.			
	Descriptions of floors, ceilings, joinery, etc. shall be deemed to include for all square cutting.			
	Carried to Summary Carpentry And Joinery			

Item No	Description	Qty	Rate	Amount
	Descriptions of items given in lineal metre shall be deemed to include for mitres, stopped ends, fitted intersections, etc.			
	Descriptions of rounded angles, rebates, grooves, chamfers, moulded edges, etc. shall be deemed to include for angles, ends, etc.			
	PRICES GENERALLY			
	Heads of screws and nails in exposed faces of joinery shall be countersunk and pelleted. All pelleting shall be done with material to suit the exposed face of the component in which it occurs.			
:	Prices for plugging are to include for approved patent wall plugs in brickwork or concrete.			
	Prices for eaves covering, ceilings, floors, joinery, etc. are to include for notching and square metre and waste.			
·	Prices for material items such as skirtings, cornices, cover strips, edge strips, etc. given in linear metre are to include for mitres, fitted intersections, stopped ends, etc.			
	Prices for labour items such as rounded angles, rebates, grooves, chamfers, moulded edges, etc. given in linear metre are to include for angles, ends, etc.			
	Carried to Summary Carpentry And Joinery			

tem No	Description		Qty	Rate	Amount
	BILL NO. 1	ja			
	CARPENTRY AND JOINERY				
	DOORS, ETC				
	Solid flush doors with 3,2 mm standard hardboard covering on both sides hung to steel frames				
1.	40mm Door 813 x 2032mm high	No	1		
	BEADS, ARCHITRAVES, ETC				
	Wrought laminated saligna				
2.	38 x 200mm Bump rail plugged	m	32		
i					
				:	
	, a				-
	Carried to Summary				
	Carpentry And Joinery				

Item No	Description	Qty	Rate	Amount
	BILL NO. 2			
#1	CEILINGS, PARTITIONS AND ACCESS FLOORING			
	PREAMBLES			
	For Preambles refer to "Standard Preambles to all trades - WB20 - 1986"			
	SUPPLEMENTARY PREAMBLES			
	TIMBER			
	All softwood to be South African pine. All hardwood to be Iroko unless otherwise specified.			
	DESCRIPTIONS			
	The term "planted on" shall mean the nailing of one timber member to another.			
	The term "screwed on" shall mean the countersunk screwing of one timber member to another.			
	The term "screwed on and pelleted" shall mean the screwing of one timber member to another with the heads of screws sunkand pelleted.			
	The term "plugged" shall mean the countersunk screwing of a timber member to and including plastic plugs in brickwork or			
	The term "plugged and pelleted" shall mean the screwing of a timber member to and including plastic plugs in brickwork or concrete with heads of screws sunk and pelleted.			
	Descriptions of floors, ceilings, joinery, etc. shall be deemed to include for all square cutting.			
	Carried to Summary Ceilings, Partitions And Access Flooring			

Item No	Description	Qty	Rate	Amount
	Descriptions of items given in lineal metre shall be deemed to include for mitres, stopped ends, fitted intersections, etc.			
	Descriptions of rounded angles, rebates, grooves, chamfers, moulded edges, etc. shall be deemed to include for angles, ends, etc.			
	PRICES GENERALLY			
	Heads of screws and nails in exposed faces of joinery shall be countersunk and pelleted. All pelleting shall be done with material to suit the exposed face of the component in which it occurs.			
	Prices for plugging are to include for approved patent wall plugs in brickwork or concrete.			
	Prices for eaves covering, ceilings, floors, joinery, etc. are to include for notching and square metre and waste.			
	Prices for material items such as skirtings, cornices, cover strips, edge strips, etc. given in linear metre are to include for mitres, fitted intersections, stopped ends, etc.			
	Prices for labour items such as rounded angles, rebates, grooves, chamfers, moulded edges, etc. given in linear metre are to include for angles, ends, etc.			
	Carried to Summary			- ::
	Ceilings, Partitions And Access Flooring			

tem No	Description	Qty	Rate	Amount
	PROPRIETARY SUSPENDED CEILINGS			
	Electrical light fittings, diffusers, panels, etc generally are "lay in" units of the same dimensions as the suspension grid described and allowance must be made accordingly for their support inclusive of any flexibility in setting out that may be required (ceiling panels have not been deducted and pricing is to take cognizance thereof)			
	PRICES GENERALLY			
×	Heads of screws and nails in exposed faces of joinery shall be countersunk and pelleted. All pelleting shall be done with material to suit the exposed face of the component in which it occurs.			
	Prices for plugging are to include for approved patent wall plugs in brickwork or concrete.			
	Prices for eaves covering, ceilings, floors, joinery, etc. are to include for notching and square metre and waste.			
	Prices for material items such as skirtings, cornices, cover strips, edge strips, etc. given in linear metre are to include for mitres, fitted intersections, stopped ends, etc.			
	Prices for labour items such as rounded angles, rebates, grooves, chamfers, moulded edges, etc. given in linear metre are to include for angles, ends,			
	etc.			
	Carried to Summary			
	Ceilings, Partitions And Access Flooring			

Item No	Description	C	Qty	Rate	Amount
140	DEMOUNTABLE PARTITIONS 50MM (NATURAL ANODISED).  Supply and fit demountable "Kappa" partition system comprising anodized aluminium UChannel fitted to suspended ceilings. Vertical split-post (mullion) to be fitted between floor and ceiling U-Channel at 1225mm c/c with angle brackets. Once framing is fixed, fit panels into place and secure with clip-on cover plates. All aluminium sections may be anodized or powder coated in a variety of colours.				
1.	Demountable Partitioning	m2 5	50		
				"	
				:	
	Carried to Summary Ceilings, Partitions And Access Flooring		_		

Item No	Description	Qty	Rate	Amount
	BILL NO. 3			
	PAINTWORK			
	PREAMBLES			
	For Preambles refer to "Standard Preambles to all trades -WB20 - 1986"		:	
	SUPPLEMENTARY PREAMBLES			
	DESCRIPTIONS			
	Descriptions of paintwork shall be deemed to include for all cutting in			
	SABS Specifications			
	Matt or eggshell decorative paint for interior works : SABS 515			
	High gloss enamel paint : SABS 630 Grade I			
	Primers for wood for internal work : SABS 678 Type			
	Undercoats for paint (except emulsion paint) : SABS 681 Type I			
	Aluminium paint : SABS 682 Grade II			
	Wash primer (metal etch) : SABS 723		_	
	Varnish for interior use : SABS 887 Type I			
	Emulsion paints : SABS 1586			
		,		
		0		
	Carried to Summary Painting			

# IMPORTANT

THIS FORM IS ONLY TO BE INCLUDED AND COMPLETED WHEN APPLICABLE TO THE QUOTATION.

# OFFICIAL BRIEFING SESSION / SITE INSPECTION CERTIFICATE

Site/building/institution involved:	MPUMELELO CLINIC				
Quotation No.:	ZNQ –				
Service:	ALTERATIONS TO ACCOMMODATE RECEPTION R				
******	*********				
(DATE) AN	OF (STATE NAME OF TENDERER)  VISITED AND INSPECTED THE SITE ON D IS THEREFORE FAMILIAR WITH THE CIRCUMSTANCES AND				
THE SCOPE OF THE SERVICE TO B	E RENDERED.				
SIGNATURE OF TENDERER OR AUTHORISED REPRESENTATIVE					
DATE :					
SIGNATURE OF DEPARTMENTAL REPRESENTATIVE					
DEPARTMENTAL STAMP:					
DATE :	••				