

| ECIFICATION NOTES | | | | | | | E ARCHITECT RIGHTS RESE | |
|--|---|---------------------------------|---------|----------------------------|-------------------|-------------------|----------------------------|----------------------------------|
| DF COVERINGS ber roof trusses with 1200 c/c detailed specifi | | Notes | | | | | | |
| ineers detail. Concealed fixing type ZincAl ga eting with Chromodeck finish of specified colo in inland areas. | our to upper | | | | | | | |
| nm thick Chromodeck roof sheeting for purlin cing. Tite 1,8mm profile as per manufacturers inst | ruction and 2 | | | | | | | |
| ction foil faced with reinforced scrim in middle abustable over purlin with galvanised straining tre spacing. | y wire at 275mm | | | | | | | |
| Ilation: 135mm thick Alucool non-combustible reinforced foil used in conjunction with strain mm centres apart & ashgrid spacer system a | ing wires at | | | | | | | |
| nufacturers installation guidelines. minium pipes | | | | | | | | |
| minium pipes and fixing straps shall be contin ned from 3003H14-3SH4 alloy strip not less th ory coated on both sides as described for alu es shall be in continuous lengths with formed es, etc. Pipes shall be fixed to walls etc with 2 ps at not exceeding 1,5m centres screwed to mm hardwood chamfered and oiled blocks pla | nan 0,7mm thick minium gutters. angles, offsets, 20 x 0,6mm 25 x 75 x | | | | | | | |
| minium gutters ninium gutters shall be continuos extruded to | | | | | | | | |
| ths and profiles from 3003H14-3SH4 alloy sti nm thick factory coated on both sides with ba two coats of silicone modified polyester to a kness of 20 micrometres finish with under gut d through fibre cement into tilting batten/gutte tia. Angles, stopped ends, etc shall be prefab riveted to gutters with joints sealed with mast ering shall be in continuous lengths between | ked enamel total minimum ter brackets r bolted to ricated units tic. The | | | | | | | |
| pped ends, etc GHTS ABOVE FLOOR LEVEL clear finished floor to ceiling heights for heal a minimum of 3,0 meters in accordance with t | | | | | | | | |
| (| SP | | S | GIGNATU | RES: DE | PT OF H | IEALTH | |
| 7170 | | | | | | | | |
| | +- | DIS | TRIC | T MANA | GER | | | |
| | | | ΓE | | | | | |
| | | | EA M | ANAGER | | | | |
| | +- | | ГE | | | | | |
| | | | | | | | | |
| WDP | | CLI | NIC | /ANAGE | R | | | |
| | | | ΓE | | | | | |
| | | | | | | | | |
| | + | Revisions | | Descriptior | 1 | | | Rev by |
| | | | | | | | | |
| | + | Checked | by Co | nsultant | | | | |
| | | Name | | | | | | |
| | | Signature Checked | | ject Leade | | | Date | |
| | | Name | - | | | | | |
| | | Signature | | | | | Date | |
| | | | n | 3 PARK C | A R LOSE HIL | | | S |
| NDP | | Client | | EL 031 765 MAIL diet | 5996 C | ELL 082 49 | 6 3518 | |
| | | | | F | | E OF K | Ith WAZULU- | NATAL |
| | | | | SIZWI 09 / 20 | _ | _ | | |
| FOR TENDER FOR OSES ONLY PURPOSES | | Drawing of CLIN | | ntion ROOI | F PLA | N | | |
| PURPOSE | | Drawn DRO Scale/s 1:10 | | | | Date 14 | 1/08/20 | 24 |
| 4m6m8m | 1 10m | Consultar | nt Drav | ving numbe OOF umber | | IS | | Revision 0 Revision |
| | | 250 | D | OOF | | IC | | 00 |

250 - ROOF PLANS